DATASHEET

Splice box sliding version 1U without front panel, unequipped, grey















General data

Material sheet steel
With sleeve nut (Art.-No. 80555.1) max. 4 splice cassettes installable
Cable entry at the rear, prepared for PG16/M20
Changeable cable entry for straight and angled
Cable entry in the middle for thinner cable

Technical properties

Depth	244.0 mm
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Sliding	sliding version
Suitable for number of module inserts	-
Width	483.0 mm
With front plate	False
With housing	True

This datasheet was created automatically on 23-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Splice box sliding version 1U without front panel, unequipped, grey

With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	RAL-number
VSB-A-GR	Splice box sliding version 1U without front panel, unequipped, grey	grey	7035
VSB-A-SW	Splice box sliding version 1U without front panel, unequipped, black	black	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION